

Delivery data (Compulsory to fill in)

Company name, contact person and telephone

Delivery address

Client code

Delegation code

Delivery date

General characteristics

Travel (R)

 mm

Load (Kg)

- 200
- 300
- 400
- 500

Power supply (±5%)

- 230V 3~ 50 hz
- 400V 3~ 50 hz
- 230V 1~ 50 hz
- Other

Traction type

- Hydraulic (Máx. travel 12000 mm)
- Electric (Máx. travel 20000 mm and máx. load 300 Kg)

Piping

- Rigid
- Flexible

N° stops

Speed (m/s)

- 0,2
- 0,3

Length

m

Lift-car characteristics

Layout N°

- 1 4
- 2 5
- 3 6
- 7

Lift-car finishing

- Baked enamel finish
- Stainless steel
- St. steel. AISI 316

Additional shelves

- Yes, Quantity
- No

Lift-car options

- Scissor car gate
- Car drop bar

Doors characteristics

Door type

- Bi-parting
- Hinged-swing

Push button denomination

Landing door finish

- Baked enamel finish
- Stainless steel
- St. steel. AISI 316

Options

- Machine room trap door (MTH elect.)
- Baked enamel finish
- Stainless steel

Boarding

- Door position 1
- Door position 2
- Door position 3

Hand

Stops with this boarding

Options

Mechanical options

- Self supporting structure
- Safety gear (walkable aisle under the pit)
- Car blocking device for maint. operations (cabine)
- Counterweight blocking device for maint. operations
- Car blocking device for maint. operations at pit area
- Pit bumper, Quantity
- Guides length 2,5 m. long.
- Machine room less (MTH Hydraulic)

Hydraulic options

- Cilinder in two pieces
- Rupture valve

Packing options

- Accesories, sling and pump unit in wooden box

Remarks

OFFER

ORDER

Dimensions

